

# **Material Safety Data Sheet**

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

## **U.S. Department of Labor**



Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

IDENTITY (As Used on Label and List) Type 3F, 3G, & 3RG Whizweld	Note: Blank spaces are not permitted. If any item is not applicable, or no information is
Branchlet	available, the space must be marked to
welding outlet fittings	indicate that.

# **Section I**

Manufacturer's Name Aegis Technologies, Inc.	Emergency Telephone Number +001.610.676.0300
Address (Number, Street, City, State, and ZIP Code)	Telephone Number for Information 1.610.676.0300 www.aegistechnologiesinc.com
319 Circle of Progress Dr	Date Prepared April 8, 2017
Pottstown, PA 19464-3811 USA	Signature of Preparer (optional)

Section II - Hazardous Ing	gredie	nts/Ide	ntity Info	rmation
Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limit Recommen	
Base Metal:				
Iron #1309-37-1 98-99%		10mg/m <sup>3</sup>	5mg/m <sup>3</sup>	none
		oxide fume	e oxide fume	
Alloying Elements:				
Carbon #7440-44-0		none	3.5mg/m3	none
0.18%			carbon bla	ck
Manganese #7439-96-5	!	5mg/m <sup>3*</sup>	5mg/m <sup>3*</sup> du	st none
0.55%			1mg/m³ fu	ıme
Silicon #7440-21-3		none	none	none
0.25%				
Phosphorus #7723-14-0		none	none	none

Phosphorus #7723-14 none none none 0.035%  $13 mg/m^3$  $5 mg/m^3$ Sulfur #7704-34-9 none 0.040% as SO<sub>2</sub> as SO<sub>2</sub>

### Metallic Coatings:\*\*

## Zinc #1314-13-2 0.050%

5mg/m3 10mg/m<sup>3</sup>dust none

5mg/m<sup>3</sup>fume

Other Coatings:

Light surface coating of rust preventative may be used. A non-metallic coating is normally applied to the product and is classified as "Protective Coating or Lubricants." The presence of this coating is not considered hazardous. Material Safety Data Sheets for these coatings are available upon request. \* Denotes "Ceiling Limit" which is not to be exceeded at any time. \*\* Galvanized product only.

# **Section III - Physical/Chemical Characteristics**

Boiling Point	>5000°F	Specific Gravity ( $H_2O = 1$ )	7.8-8.2 @60°F approx.
Vapor Pressure (mm Hg)	N/A	Melting Point	2500°F approx. base 900°F approx. coat**
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water INSO	UBLE		·

Appearance and Odor SOLID, DARK GRAY, and ODORLESS

# **Section IV - Fire and Explosion Hazard Data**

Flash Point (Method Used) Not applicable in solid state	Flammable Limits <b>N/A</b>	LEL N/A	UEL N/A	
Extinguishing Media N/A				
Special Fire Fighting Procedures N/A				
Unusual Fire and Explosion Hazards N/A				

(Reproduce locally)

## OSHA 174, Sept. 1985

# **Section V - Reactivity Data**

Stability	Unstable	No	Conditions to Avoid N/A	
	Stable	Yes		
Incompatibility	(Materials to	Avoid) <b>N/</b>	A	
Hazardous Decomposition or Byproducts N/A				
HazardousMay OccurNoConditions to AvoidN/APolymerizationNoNoNoNo				
	Will Not Occur	Yes		

# Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? N/A	Skin? <b>Yes</b>	Ingestion? N/A		
Health Hazards (Acute and Chronic)					

Skin irritation may result from prolonged contact with the coating of	rust
preventative.	

Carcinogenicity:

N/A IARC Monographs? N/A

OSHA Regulated? N/A

Regulated? N/A

Signs and Symptoms of Exposure

NTP?

#### Skin irritation

Medical Conditions

Generally Aggravated by Exposure

Skin irritation may result from prolonged contact with the coating of rust preventative.

Emergency and First Aid Procedures

For skin irritation, wash the contaminated area with mild soap and water.

# **Section VII - Precautions for Safe Handling and Use**

Steps to Be Taken in Case Material is Released or Spilled N/A

Waste Disposal Method N/A

Precautions to Be taken in Handling and Storing Skin irritation may result from prolonged contact with the coating of rust preventative.

Skin nicks and cuts may result from burrs after modifying the product length in the field.

Other Precautions N/A

# **Section VIII - Control Measures**

Respiratory Protection (Specify Type) N/A

Ventilation	/entilation Local Exhaust Reference Work/Hygienic Practices		I
	Mechanical (General) Reference Work/Hygienic Practices	Other N/A	
	oves ded if prolonged contact duct length modification is	Eye Protectior <b>Recommend</b>	
Other Protect	tive Clothing or Equipment N/A		
Work/Hygien	ic Practices <b>N/A</b>		

\* U.S.G.P.O.: 1986 - 491 - 529/45775